

DART SERVICE INSTRUCTION

TO AMEND INSTALLATION INSTRUCTIONS IIN-D412-760 REV. G OR LATER APPROVED REVISION AND INSTRUCTIONS FOR CONTINUED AIRWORTHINESS ICA-D412-760 REV. 5 OR LATER APPROVED REVISION

REF. TCCA STC: SH07-37
REF. FAA STC: SR02492NY
REF. EASA STC: IM.R.S.01361
REF. ANAC STC: 2009S08-18
REF. ANAC STC: 2009S08-19
REF. ANAC STC: 2009S08-20

1.0 PURPOSE:

The purpose of this Dart Service Instruction (DSI) is to provide customers that have purchased the D412-760-011/-013/-015/-017/-019 with the option to install a traction strip kit.

The D412-760-311 Kit provides the customer with 27 strips of black self adhesive traction tape, qty (18) 2" X 14" (51mm X 356mm) and qty (9) 2" x 10" (51mm X 254mm).

It is permissible to install more than one kit in a single aircraft if the operator wishes to have more coverage.

2.0 INSTALLATION PROCEDURE:

2.1 The number and location of D5538-1/-3 Traction Strips are to be applied at the installers discretion. Figure 1 is a suggested configuration which covers the "high traffic" areas of the passenger cabin.

Note: In the configuration shown in Figure 1, (24) Traction Strips are used (16) Standard and (8) Short. There will be (3) spare strips, (2) Standard and (1) Short.

2.2 Traction Strips must be applied to the textured face of the Cabin Floor Protector Panels.

2.3 Ensure the textured surface is clean and free of dirt and/or debris. Clean surfaces with Isopropyl alcohol.

2.4 Locate the D5538-1/-3 Traction Strips in the desired location. The Traction Strips should be located 0.25" - 0.50" (6mm - 13mm) from the edge of the cabin floor protectors as shown in Figure 1 Detail A, to prevent the Traction Strip from peeling.

2.5 If the Traction Strip is located on one of the "voids" on the cabin floor protectors, as shown in Figure 1 Detail A, transfer mark the shape of the "void" to the back face of the Traction Strip and trim the strip, prior to installing the Traction Strip. Ensure that the edge of the strip is 0.25" - 0.50" (6mm - 13mm) from edge of the "void" as shown Figure 1 Detail A to prevent peeling.

2.6 Peel back the backing and install the tape section.

Note: Tape will stick immediately. It is not acceptable to remove and reapply.

2.7 Press on the tape section and smooth out any air bubbles.

2.8 Update the Aircraft log book to record installation of the D412-760-311 Traction Strip Kit.

CANADA
DEPARTMENT OF TRANSPORT
AIRCRAFT CERTIFICATION
BRANCH
DAO # 01-O-01

APPROVED
BY: 
D. SHEPHERD (DE # 02)

DATE: 17.05.09
CERT. NO.: SH07-37
ISSUE NO.: 3

APPROVED

A	NEW ISSUE	AJS	17.05.09
REV.	DESCRIPTION	BY	DATE
DESIGN	AJS	DART AEROSPACE LTD HAWKESBURY, ONTARIO, CANADA	
DRAWN	AJS		
CHECKED	WM	DRAWING NO.	REV. A
MFG. APPR.	N/A	DSI 9780	SHEET 1 OF 3
APPROVED	WM	TITLE	SCALE
DE APPR.	DS	TRACTION STRIP KIT	NTS
DATE	17.05.09	COPYRIGHT © 2017 BY DART AEROSPACE LTD. THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE LTD.	

3.0 PARTS LIST:

ITEM	QTY -311	P/N	DESCRIPTION
	X	D412-760-311	TRACTION STRIP KIT, BLACK
1	18	D5538-1	TRACTION STRIP (BLACK)
2	9	D5538-3	SHORT TRACTION STRIP (BLACK)

4.0 WEIGHT AND BALANCE:

The material used in the D5538-1/-3 Traction Strips weighs 0.15 lbs per sq ft (0.73 kgs per sq m).

Each D5538-1 Traction Strip weighs approximately 0.03 lbs (0.014 kgs).

Each D5538-3 Traction Strip weighs approximately 0.02 lbs (0.009 kgs).

A complete D412-760-311 Traction Strip Kit weighs approximately 0.63 lbs (0.29 kgs). The Aircraft Weight and Balance should be updated accordingly by the installer.


CANADA
DEPARTMENT OF TRANSPORT
AIRCRAFT CERTIFICATION
BRANCH
DAO # 01-O-01

APPROVED

BY: 
D. SHEPHERD (DE # 02)

DATE: 17.05.09
CERT. NO.: SH07-37
ISSUE NO.: 3

APPROVED

DESIGN	AJS	DART AEROSPACE LTD HAWKESBURY, ONTARIO, CANADA
DRAWN	AJS	
CHECKED	WM	DRAWING NO. REV. A
MFG. APPR.	N/A	DSI 9780 SHEET 2 OF 3
APPROVED	WM	TITLE SCALE
DE APPR.	DS 	TRACTION STRIP KIT NTS
DATE	17.05.09	COPYRIGHT © 2017 BY DART AEROSPACE LTD THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE LTD.






FIGURE 1:D412-760-311 TRACTION STRIP INSTALLATION
SUGGESTED INSTALLATION CONFIGURATION ONLY
QUANTITY AND LOCATION OF TRACTION STRIPS USED ARE AT THE OPERATOR'S DISCRETION
(SHOWN INSTALLED ON D412-760-011 INSTALLATION ON D412-760-013/-015/-017/-019 KITS SIMILAR)
(TYPICAL SEATING CONFIGURATION SHOWN FOR REF ONLY)

CANADA
DEPARTMENT OF TRANSPORT
AIRCRAFT CERTIFICATION
BRANCH
DAO # 01-O-01

APPROVED
BY: *[Signature]*
D. SHEPHERD (DE # 02)

DATE: 17.05.09
CERT. NO.: SH07-37
ISSUE NO.: 3

APPROVED

DESIGN	AJS	DART AEROSPACE LTD HAWKESBURY, ONTARIO, CANADA	
DRAWN	AJS		
CHECKED	WM	DRAWING NO.	REV. A
MFG. APPR.	N/A	DSI 9780	SHEET 3 OF 3
APPROVED	WM	TITLE	SCALE
DE APPR.	DSC	TRACTION STRIP KIT	NTS
DATE	17.05.09	COPYRIGHT © 2017 BY DART AEROSPACE LTD <small>THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE LTD.</small>	